



PRODUCT ELEMENTS - PERFORATED

	Stock Code	OD	A	T	H	P	OPEN AREA %
2" Product Element - 1mm	2340440	46.5	400	0.9	1.0	2.0	22.7%
2" Product Element - 1.5mm	2340455	46.5	400	0.9	1.5	3.0	22.7%
2" Product Element - 2mm	2340484	46.5	400	0.9	2.0	4.0	22.7%
2" Product Element - 3mm	2340465	46.5	400	0.9	3.0	5.0	32.7%
2" Product Element - 5mm	2340490	46.5	400	0.9	5.0	8.0	35.5%
3" Product Element - 1mm	2340450	72	502	0.9	1.0	2.0	22.7%
3" Product Element - 1.5mm	2340460	72	502	0.9	1.5	3.0	22.7%
3" Product Element - 2mm	2340482	72	502	0.9	2.0	4.0	22.7%
3" Product Element - 3mm	2340470	72	502	0.9	3.0	5.0	32.7%
3" Product Element - 5mm	2340491	72	502	0.9	5.0	8.0	35.5%
3" Product Element - 10mm	2340480	72	502	0.9	10.0	15.0	40.4%
4" Product Element - 1mm	2340452	97	525	0.9	1.0	2.0	22.7%
4" Product Element - 1.5mm	2340462	97	525	0.9	1.5	3.0	22.7%
4" Product Element - 3mm	2340472	97	525	0.9	3.0	5.0	32.7%
4" Product Element - 5mm	2340492	97	525	0.9	5.0	8.0	35.5%
6" Product Element - 1mm	2340453	149	600	0.9	1.0	2.0	22.7%
6" Product Element - 1.5mm	2340463	149	600	0.9	1.5	3.0	22.7%
6" Product Element - 3mm	2340473	149	600	0.9	3.0	5.0	32.7%

- MANUFACTURED BY BSF - FROM 316 STAINLESS STEEL
- ELEMENT ASSEMBLY CONSISTS OF:
1 X PERFORATED ELEMENT, 1 X CLAMP BLANK
- ROUND PERFORATION:
STAGGERED PITCH @ 60 DEGREES
- SUITABLE FOR CIP & SIP SYSTEMS.

- RIGID ELEMENTS SUITABLE FOR REVERSE FLUSHING.
- INNER & OUTER FINE MESH WRAP CAN BE SUPPLIED ON REQUEST.
- OTHER PERFORATION SIZES & PATTERNS AVAILABLE ON REQUEST.
- PERFORATED ELEMENTS ARE SUITABLE FOR FLOW IN TO OUT, AND FLOW OUT TO IN.