



## PUMP PROTECTION ELEMENTS - PERFORATED

	Stock Code	OD	A	T	H	P	OPEN AREA %
<b>2" Pump Element - 1mm</b>	2320220	46.5	130	0.9	1.0	2.0	22.7%
<b>2" Pump Element - 1.5mm</b>	2320420	46.5	130	0.9	1.5	3.0	22.7%
<b>2" Pump Element - 2mm</b>	2320221	46.5	130	0.9	2.0	4.0	22.7%
<b>2" Pump Element - 3mm</b>	2320620	46.5	130	0.9	3.0	5.0	32.7%
<b>2" Pump Element - 4mm</b>	2320222	46.5	130	0.9	4.0	6.0	40.4%
<b>2" Pump Element - 5mm</b>	2320635	46.5	130	0.9	5.0	8.0	35.5%
<b>3" Pump Element - 1mm</b>	2320230	72	205	0.9	1.0	2.0	22.7%
<b>3" Pump Element - 1.5mm</b>	2320430	72	205	0.9	1.0	3.0	22.7%
<b>3" Pump Element - 2mm</b>	2320235	72	205	0.9	2.0	4.0	22.7%
<b>3" Pump Element - 3mm</b>	2320630	72	205	0.9	3.0	5.0	32.7%
<b>3" Pump Element - 5mm</b>	2320636	72	205	0.9	5.0	8.0	35.5%
<b>4" Pump Element - 1mm</b>	2320240	97	238	0.9	1.0	2.0	22.7%
<b>4" Pump Element - 1.5mm</b>	2320435	97	238	0.9	1.5	3.0	22.7%
<b>4" Pump Element - 2mm</b>	2320631	97	238	0.9	2.0	4.0	22.7%
<b>4" Pump Element - 3mm</b>	2320632	97	238	0.9	3.0	5.0	32.7%
<b>4" Pump Element - 5mm</b>	2320639	97	238	0.9	5.0	8.0	35.5%
<b>6" Pump Element - 1mm</b>	2320250	149	323	0.9	1.0	2.0	22.7%
<b>6" Pump Element - 1.5mm</b>	2320440	149	323	0.9	1.5	3.0	22.7%
<b>6" Pump Element - 3mm</b>	2320634	149	323	0.9	3.0	5.0	32.7%

- MANUFACTURED BY BSF - FROM 316 STAINLESS STEEL
- ELEMENT ASSEMBLY CONSISTS OF:  
1 X PERFORATED ELEMENT, 1 X CLAMP BLANK
- ROUND PERFORATION:  
STAGGERED PITCH @ 60 DEGREES
- SUITABLE FOR CIP & SIP SYSTEMS.

- RIGID ELEMENTS SUITABLE FOR REVERSE FLUSHING.
- INNER & OUTER FINE MESH WRAP CAN BE SUPPLIED ON REQUEST.
- OTHER PERFORATION SIZES & PATTERNS AVAILABLE ON REQUEST.
- PERFORATED ELEMENTS ARE SUITABLE FOR FLOW IN TO OUT, AND FLOW OUT TO IN.