



PUMP PROTECTION Y TYPE STRAINER BODY 316L

	1"	1.5"	2"	2.5"	3"	4"	6"
Code: OD Ends	2300410	2300415	2300420	2300425	2300430	2300440	2300445
Code: RJT M/M	2300210	2300215	2300220	2300225	2300230	2300240	-
Code: Clamp End	2300250	2300255	2300260	2300265	2300270	2300275	2300280
A	297	266	191	380	300	473	540*
B	125	125	125	193	193	232	317.5
OD	25.4	38.1	50.8	63.5	76.2	101.6	154

Above Dimensions is based on a OD Weld Ended Strainer.

THE PUMP PROTECTION "Y" STRAINER IS DESIGNED SPECIFICALLY TO REMOVE POTENTIALLY DAMAGING DEBRIS BEFORE IT PASSES THROUGH THE PUMP, HOWEVER IT IS NOW WIDELY USED AS A STRAINER FOR COARSE PARTICLES ENTERING PRODUCT LINES, IT IS DESIGNED TO FIT INTO CONFINED SPACES, AS WELL AS FOR EASE OF CLEANING AND THE CHANGING OF ELEMENTS.

PUMP PROTECTION "Y" STRAINER:

- DESIGNED & MANUFACTURED BY BERKELEY STAINLESS FITTINGS LTD - ENTIRELY FROM 316 STAINLESS STEEL.
- NO TOOLS REQUIRED FOR DISMANTLING.
- PUMP PROTECTION BODY KIT CONSISTS OF: 1 X BODY. 1 X SINGLE HINGED CLAMP & 1 X LIPPED EDPM JOINT RING.
- TO MAKE EITHER 1", 1.5" OR 2.5" INLET/OUTLET - A CONCENTRIC CONE WILL BE USED ON A STANDARD BODY SEE PAGE 28 FOR CONE LENGTHS.
- SHUT OFF VALVES CAN BE WELDED TO THE UNIT.
- STANDARD FINISH - 240 GRIT ID & OD - OTHER FINISHES AVAILABLE ON REQUEST.
- ELEMENTS - WE STOCK A WIDE RANGE OF PERFORATED & WEDGE WIRE ELEMENTS - SEE ELEMENTS PAGE 54 & 56.
- WE STRONGLY RECOMMEND ORDERING A REPLACEMENT ELEMENT TO EASE CLEANING AND TO MINIMIZE LINE DOWN TIME.

OPTIONAL ENDS ARE AVAILABLE ON A SHORT DELIVERY.

Jacketed & Duplex strainers can be supplied to the customer's specification

DUE TO CONTINUOUS DEVELOPMENT & INNOVATION, WE RESERVE THE RIGHT TO CHANGE THE DESIGN/DIMENSIONS WITHOUT PRIOR NOTICE